



TWINAXIAL SPEAKER CABLES REFLEX



TS 240 / TS 440

✓ MOBILE ✓ STUDIO ✓ INSTALLATION ✓ STAGE

sPVC

OFC

ANALOG

TS 640 / TS 840

APPLICATION

These reflex professional speaker cables are originally designed to deliver maximum performance from state-of-the-art Tri-Amp Systems. Extra-tough jacket and oversized heavy-duty construction for exceptional ruggedness and durability.

CONSTRUCTION DATA

Core Section	4 mm ²
Stranded Copper Conductor	224 x 0,15 mm ø Stranded Bare Copper (16 AWG)
Conductor Insulation	3,90 ± 0,05 mm ø PVC
Conductor Color Code	Blue / Red / Yellow / Green / Black / Pink / Orange / White

	TS 240	TS 440	TS 640	TS 840
Core Numbers x Section	2 x 4,0 mm ²	4 x 4,0 mm ²	6 x 4,0 mm ²	8 x 4,0 mm ²
Outer Sheath	sPVC Matt Black	sPVC Matt Black	sPVC Matt Black	sPVC Matt Black
Outer Diameter	9,60 ± 0,10 mm ø	11,50 ± 0,10 mm ø	14,8 ± 0,10 mm ø	18 ± 0,10 mm ø
Weight	15,8 kg/100 m	27,7 kg/100 m	43,5 kg/100 m	60 kg/100 m

ELECTRICAL DATA

Conductor Resistance	< 4,45 Ω / km
Insulation Resistance	> 2000 MΩ x km
Capacitance	
	core/core
	180 pF / m
Inductance	0.5 μH / m
Test voltage	2 kV
Max. Operating Voltage	300 V

MECHANICAL DATA

Minimum bending radius	5 x D (D= outer diameter)
Temperature range	
Mobile installation	- 5° C to + 70° C
Fixed installation	-30° C to + 70° C

■ BLACK

