



FLAT INSTALLATION CABLES

VF 224 FLAT

✓ MOBILE ✓ STUDIO ✓ INSTALLATION ✓ STAGE



APPLICATION

VF 224 cable is designed to be used in TV channels and mobile installations where flat cables are required. This cable is specially suitable for connecting, high ohmic components such as favourite media device keyboards professional stage and studio operation

CONSTRUCTION DATA

Core Numbers x Section	2 x 0,22 mm ² (AWG 24)
Stranded Copper Conductor	28 x 0,10 mm \varnothing Stranded Bare Copper
Conductor Insulation	1,50 \pm 0,05 mm \varnothing PE
Conductor Color Code	Blue / Red
Shielding Factor	Copper spiral shielding
Shielding Factor	100%
Outer Sheath	sPVC
Outer Diameter	3,1 x 6,1 mm \varnothing
Weight	3 kg/100 m

ELECTRICAL DATA

Conductor Resistance	< 86 Ω / km
Shield Resistance	< 39 Ω / km
Insulation Resistance	> 2000 M Ω x km
Capacitance core/core	80 pF / m
core/screen	150 pF / m

MECHANICAL DATA

Minimum bending radius	10 x D (D= outer diameter)
Temperature range	
Mobile installation	- 5° C to + 70° C
Fixed installation	-30° C to + 70° C

■ BLACK

