



ANALOG PATCH AUDIO CABLES BALANCED



VP 203 PRO SHINE ✓STUDIO ✓INSTALLATION

PVC OFC ANALOG

APPLICATION

Broadcast standard balanced audio cable for permanent installation. OFC copper conductors are easy to solder or punch-down. Excellent process control and tight pair twisting achieves superior noise rejection. Best shields and critical is an environment of high RF and EMI. Ideal for punch-down, rack wiring, and extended distance runs of mic level signals.

CONSTRUCTION DATA

Core Numbers x Section	2 x 0,20 mm ² (AWG 24)
Stranded Copper Conductor	25 x 0,10 mm Ø Stranded bare copper
Conductor Insulation	1,20 ± 0,05 mm Ø XLPE
Conductor Color Code	Blue / Red
Shielding	Copper spiral shielding
Shielding Factor	100%
Outer Sheath	PVC
Outer Diameter	3,2 mm Ø
Weight	1.9 kg/100 m

ELECTRICAL DATA

Conductor Resistance	< 86 Ω / km
Shield Resistance	< 39 Ω / km
Insulation Resistance	> 2000 MΩ x km
Capacitance	core/core 65 pF / m
	core/screen 130 pF / m
Nominal Impedance 1 KHz	600 Ω /100 m

MECHANICAL DATA

Minimum bending radius	10 x D (D= outer diameter)
Temperature range	-30° C to + 70° C

■ BLACK

