



ANALOG PATCH AUDIO CABLES BALANCED

VP 223 SWAN LSZH

✓STUDIO ✓INSTALLATION



APPLICATION

Industry standard balanced audio cable for permanent installation. Stranded tinned-copper conductors are easy to solder or punch-down. Excellent process control and tight pair twisting achieves superior noise rejection. Ideal for punch-down, rack wiring, and extended distance runs of mic level signals. These cable products have low smoke density, halogen free and they don't emit poisonous gases.

CONSTRUCTION DATA

Core Numbers x Section	2 x 0,22 mm ² (AWG 24)
Stranded Copper Conductor	7 x 0,20 mm ø Tinned copper
Conductor Insulation	1,20 ± 0,05 mm ø XLPE
Conductor Color Code	Blue / Red
Stranded Drain Wire	7 x 0,20 mm ø Tinned copper
Shielding	Al / Pes - Foil
Shielding Factor	100%
Outer Sheath	HFFR Compound
Outer Diameter	3,0 mm ø
Weight	1.6 kg/100 m

ELECTRICAL DATA

Conductor Resistance	< 86 Ω / km
Shield Resistance	< 75 Ω / km
Insulation Resistance	> 2000 MΩ x km
Capacitance	core/core 75 pF / m
	core/screen 130 pF / m
Nominal Impedance 1 KHz	600 Ω /100 m

MECHANICAL DATA

Minimum bending radius	10 x D (D= outer diameter)
Temperature range	-30° C to + 70° C

■ BLACK

